



ADDRESS SIGN STANDARDS

ADDRESS SIGNS:

- Address numbers and letters shall be a minimum of:
 - Four (4) inches high
 - 1/2 inch stroke
 - ReflectORIZED on a contrasting background color. The preferred color is white letters/numbers on a green background.
- Posts used to mount addresses must be fire retardant (metal, concrete, masonry, pressure treated wooden 4 inch by 4 inch post).
- Addresses must be mounted a minimum of 32 inches above the ground (higher in snow country).
- Street names must be mounted a minimum of seven (7) feet above the ground.
- If your street address does not match the name of the road you live on, post your full address (number and street name).

LOCATION OF ADDRESS SIGNS:

- **All residents or commercial buildings shall display an address sign.**
- A second address sign must be posted at the intersection of the driveway and the roadway if the address on the building is not visible for a minimum of 100 feet. This second address sign must be visible a minimum of 100 feet, both directions, along the roadway.
- Where multiple addresses are accessed by a single driveway or unnamed roadway, **ALL** addresses shall be posted on a single sign/post visible a minimum of 100 feet, both directions along the roadway.
- Additional address sign(s) are required when driveways or unnamed roads intersect or fork and it is not readily apparent which direction leads to the address(es).

HELP US FIND YOU SO WE CAN HELP YOU!